

ConSeal™ CS-50

Solventborne Liquid Butyl Primer

Surface Preparation Coating and Installation Aid for Concrete and Metal Surfaces

Applications

For use on concrete or metal surfaces, CS-50 Solventborne Surface Primer is a concrete surface preparation coating and installation aid for bonding preformed sealants. CS-50 Solventborne Surface Primer can be applied in advance of product installation.

Sealing Properties

When applied to concrete or metal, ConSeal CS-50 Liquid Butyl Primer creates a butyl rubber film that acts to both seal the structure and improve the bond of preformed sealants.

Physical Properties

Description	CS-50
Color:	Black
% Solids:	20% minimum
Solvent Type:	VMP Naphtha
Flash Point:	76°F
Weight / Gallon:	7.5 Pounds
Dry Time @ 77°F (25°C):	15-20 minutes
Dry Time @ 40°F (4°C):	30-40 minutes
Clean Up:	Mineral Spirits
Coverage Per Gallon:	Approx. 300 sq ft on wet cast concrete.
Min. Storage Temperature:	32°F
Min. Application Temperature:	0°F
Surface When Dry:	Flat Black, non-tacky
Shelf Life:	2 years

Limited Warranty

This information is presented in good faith, but we cannot anticipate all conditions under which this information and our products, or the products of other manufactures in combination with our products, may be used. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products, either alone or in combination with other products. Users are advised to make their own tests to determine the safety and suitability of each such product combinations for their own purposes. It is the **users' responsibility** to satisfy himself as to the suitability and completeness of such information for this own particular use. We sell this product without warranty, and buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of this product, whether used alone or in combination with other products.



Version: 12-Feb-20 © 2020 Concrete Sealants, Inc.

