



January 4, 2021

Certificate of Conformance

This is to certify that the material listed below conforms to the following specifications. The material meets or exceeds the listed performance requirements.

Product: ConSeal CS-1800 Solvent-Free, Waterproofing Membrane

Performance: Solvent and Isocyanate-free. California Proposition 65 compliant. 1/8" cure every 24 hours at 77°F and 50% RH. No measurable shrinkage after 14 days.

Specifications: This product meets the requirements of ASTM C836. It has positive waterproofing capabilities up to 100 psi (ASTM D5385)

Chemical Composition and Properties:

Tensile Strength, typical (ASTM D412)	113 psi
Elongation, typical (ASTM D412)	535 %
Shear Strength, typical (ASTM D1002)	132 psi
Shore OO Hardness, typical (ASTM D2240)	67

Pursuant to the provisions of the Buy American Act (BAA) under Section 1605 of the American Recovery and Reinvestment Act (ARRA), all preformed sealant tapes, concrete admixtures, elastomeric sealants, elastomeric membranes and concrete coatings sold by Concrete Sealants, Inc. qualify as goods produced in the United States. All components of these products are manufactured in Tipp City, Ohio using various raw materials, also purchased in the United States.

Sincerely,

Van R. Foster
Research and Development Director,
Concrete Sealants, Inc.