

Strong Green Strength, Instant Grab Adhesive-Sealant for Concrete

APPLICATIONS

Designed as a single component, gun-grade, non-sagging, moisture-activated mounting adhesive-sealant which forms a quick tack bond with strong green strength and instantly provides bonding without need for additional support. CS-1550 can be used for new construction and repair applications, such as: adhesive for preformed sealants, joining concrete risers and blocks, and more!



PERFORMANCE PROPERTIES

Features

- Finish: White, Mildew Resistant, Elastomer
- Solvent & Isocyanate Free, 100% Solids, Will Not Shrink
- California Proposition 65 compliant
- Tack free skin forms in 40 minutes (77°F at 50% Relative Humidity)
- Full cure takes place in 24 to 48 hours for 1/4" beads and smaller.
- Excellent weatherability when exposed to: Ultraviolet Radiation, Rain, Infrared Radiation, and Atmospheric Hydrocarbons.
- CS-1550 can be painted with emulsion or synthetic enamel paints.
- Resilient elastomer that adheres to most construction materials, including: Concrete, Metal, Fiberglass, Plastic, PVC, Glass, Aluminum and Wood.

PHYSICAL PROPERTIES

Property	CS-1550 Value	Test Method
Cure System	Hybrid, Moisture Cure	
VOC Content	75.5 grams/liter	
Cure Rate (77°F at 50% Relative Humidity)	1/8" every 24 hours	
Gun Grade	Zero Slump	ASTM C639

PERFORMANCE CHARACTERISTICS

Property	CS-1550 Value	Test Method
Tensile Strength	469 psi	ASTM D412
Elongation	162%	ASTM D412
Shore A, Hardness	43	ASTM D661
UV Stability, Accelerated Weathering	UV-A, No Change (2,000 hours)	QUV Weatherometer
Shrinkage	No measureable shrinkage after 14 days	
Service Temperature	-40°F to 220°F (-40°C to 104°C), continuous service	
Application Ambient Temperature	40°F to 130°F (4°C to 55°C)	
Application Surface Temperature	40°F to 130°F (4°C to 55°C)	

DO NOT USE PETROLEUM SOLVENTS SUCH AS MINERAL SPIRITS OR XYLENE FOR SURFACE PREPARATION.

DIRECTIONS FOR USE

Surface Preparation: The concrete must be clean and free from dust, dirt, grease and debris before application of CS-1550. Inspect surface for soundness. When surface is clean, sound and dry proceed with using the CS-1550.

Note: Make sure the surface is free from frost prior to application.

Priming: For applications with continuous water immersion ConSeal recommends using a surface primer. ConSeal CS-80 and CS-85 are specifically designed for ConSeal's elastomeric sealants.

Application Instructions: Maintain CS-1550 at room temperature before applying to ensure easy application. CS-1550 may be factory or field applied to seal various construction components. Work CS-1550 into rough surfaces to optimize surface contact.

Sealant Adhesive Instructions: For any sizes of ConSeal preformed joint sealants, place a 3/8" diameter bead to concrete surface to which the sealant will be applied. After applying the CS-1550, immediately press the preformed sealant into CS-1550 to adhere the preformed sealant to the concrete joint surface.

Packaging and Storage: Available in 9.5-fl. oz. cartridges (280mL) and 20.2-fl. oz sausages (600mL).

12-month shelf life from manufacture date when stored in a cool, dry area. Elevated temperatures >100° F may reduce shelf life.

Coverage and Full Cure Rates: 9.5-ounce cartridges: 3/8" diameter bead covers 12 linear feet. Full cure for 1/4" bead is 48 hours (77°F at 50% Relative Humidity).

LIMITED WARRANTY

This information is presented in good faith, but we cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with our products, may be used. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products, either alone or in combination with other products. Users are advised to make their own tests to determine the safety and suitability of each such product or product combinations for their own purposes. It is the users' responsibility to satisfy himself as to the suitability and completeness of such information for this own particular use. We sell this product without warranty, and buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of this product, whether used alone or in combination with other products.

© 2022 CONCRETE SEALANTS, INC.

CONCRETE SEALANTS, INC. | 9325 STATE ROUTE 201, TIPP CITY, OH 45371, USA | WWW.CONSEAL.COM

USA | CANADA +1.800.332.7325 | INTERNATIONAL +1.937.845.8776

VERSION: 7-APR-2022



CONCRETE SEALANTS, INC.
ISO 9001:2015 REGISTERED