

July 3, 2023

## Certificate of Conformance

This is to certify that the material listed below conforms to the following specifications. The material meets or exceeds the listed performance requirements.

**Product:** ConSeal CS-1500 SL Rapid-Cure Self-Leveling Elastomeric Sealant

**Specifications:** This product meets the requirements of ASTM C920, Type S, Grade P, Class 50, Uses T1, M, G, A and O.

**Performance:** Solvent and Isocyanate-free. California Proposition 65 compliant. 24-48 hour full cure at 77°F and 50% RH for ¼" bead or smaller. No measurable shrinkage after 14 days.

### Chemical Composition and Properties:

Tensile Strength, typical (ASTM D412)	143 psi
Elongation, typical (ASTM D412)	176%
Shear Strength, typical (ASTM D1002)	194 psi
Shore A Hardness, typical (ASTM D661)	24

Pursuant to the provisions of the Buy American Act (BAA) under Section 1605 of the American Recovery and Reinvestment Act (ARRA), all preformed sealant tapes, concrete admixtures and concrete coatings sold by Concrete Sealants, Inc. qualify as goods produced in the United States. All components of these products are manufactured in Tipp City, Ohio using various raw materials, also purchased in the United States.

Sincerely,



Van R. Foster  
Research and Development Director,  
Concrete Sealants, Inc.