

All-Weather Surface Preparation Coating and Installation Aid for Concrete and Metal Surfaces

APPLICATIONS

Installation aid for bonding preformed sealants in wet conditions or frozen concrete structures.

SEALING PROPERTIES

CS-300 surface primer has the ability to create a bond on wet concrete surfaces. CS-300 is ideal when working in extreme weather conditions such as freezing temperatures or heavy rain.

PHYSICAL PROPERTIES

Color:	Light Amber
% Solids:	18% ±2%
Solvent Type:	Hexane
Flash Point:	-20°F
Weight per Gallon:	5.9 lbs./gal
Dry Time @ 77°F (25 C):	15 minutes or less
Dry Time @ 40°F (4 C):	15 minutes
Clean Up:	Mineral Spirits
Coverage per Gallon:	Approximately 300 sq. ft on wet cast concrete.
Min. Storage Temperature:	40°F-80°F
Surface when dry:	Tacky



DIRECTIONS FOR USE

Surface Preparation: The concrete must be clean and free from dust, dirt, grease and debris before application of CS-300. Inspect surface for soundness. Repair or remove any surface irregularities and loose concrete, using an approved crack filling method on static hairline cracks. When the surface is clean, sound and dry, proceed with coating application.

Application: Apply an even coating of the primer to the desired concrete surface and allow it to dry. A second coat may be needed if there are any surface voids noticed or the concrete surface appears to have any sections that are uncoated. Once the surface is dry, apply the sealant to the coated surface. Replace the cap on the primer immediately after use.

LIMITED WARRANTY

This information is presented in good faith, but we cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with our products, may be used. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products, either alone or in combination with other products. Users are advised to make their own tests to determine the safety and suitability of each such product or product combinations for their own purposes. It is the users' responsibility to satisfy himself as to the suitability and completeness of such information for this own particular use. We sell this product without warranty, and buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of this product, whether used alone or in combination with other products.

© 2022 CONCRETE SEALANTS, INC.

CONCRETE SEALANTS, INC. | 9325 STATE ROUTE 201, TIPP CITY, OH 45371, USA | WWW.CONSEAL.COM

USA | CANADA +1.800.332.7325 | INTERNATIONAL +1.937.845.8776

VERSION: 7-APR-2022



CONCRETE SEALANTS, INC.
ISO 9001:2015 REGISTERED