

Surface Preparation Coating and Installation Aid for Concrete and Metal Surfaces

APPLICATIONS

For use on concrete or metal surfaces, CS-50 Solventborne Surface Primer is a concrete surface preparation coating and installation aid for bonding preformed sealants. CS-50 Solventborne Surface Primer can be applied in advance of product installation.

SEALING PROPERTIES

When applied to concrete or metal, ConSeal CS-50 Liquid Butyl Primer creates a butyl rubber film that acts to both seal the structure and improve the bond of preformed sealants.

PHYSICAL PROPERTIES

Description	CS-50
Color:	Black
% Solids:	20% minimum
Solvent Type:	VM&P Naphtha
Flash Point:	76°F
Weight / Gallon:	7.5 lbs./gal
Dry Time @ 77°F (25°C):	15-20 minutes
Dry Time @ 40°F (4°C):	30-40 minutes
Clean Up:	Mineral Spirits
Coverage Per Gallon:	Approx. 250 square feet
Min. Storage Temperature:	32°F (0°C)
Min. Application Temperature:	0°F (-18°C)
Surface When Dry:	Flat Black, non-tacky
Shelf Life:	2 years



DIRECTIONS FOR USE

Surface Preparation: The concrete must be clean and free from dust, dirt, grease and debris before application of CS-50. Inspect surface for soundness. Repair or remove any surface irregularities and loose concrete, using an approved crack filling method on static hairline cracks. When the surface is clean, sound and dry, proceed with coating application.

Application: Apply an even coating of the primer to the desired concrete surface and allow it to dry. A second coat may be needed if there are any surface voids noticed or the concrete surface appears to have any sections that are uncoated. Once the surface is dry, apply the sealant to the coated surface. Replace the cap on the primer immediately after use.

LIMITED WARRANTY

This information is presented in good faith, but we cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with our products, may be used. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products, either alone or in combination with other products. Users are advised to make their own tests to determine the safety and suitability of each such product or product combinations for their own purposes. It is the users' responsibility to satisfy himself as to the suitability and completeness of such information for this own particular use. We sell this product without warranty, and buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of this product, whether used alone or in combination with other products.

© 2024 CONCRETE SEALANTS, INC.

CONCRETE SEALANTS, INC. | 9325 STATE ROUTE 201, TIPP CITY, OH 45371, USA | WWW.CONSEAL.COM

USA | CANADA +1.800.332.7325 INTERNATIONAL +1.937.845.8776

VERSION: 16--OCT-2024



CONCRETE SEALANTS, INC.
ISO 9001:2015 REGISTERED