



SEAL OF SECURITY. BOND OF TRUST.

ConSeal™ CS-80

CONCRETE PRIMER FOR ELASTOMERIC SEALANTS

Concrete Surface Preparation Coating for Bonding Elastomeric Sealants

APPLICATIONS

For use on concrete surfaces for elastomeric sealants immersed in water or subgrade applications.

PERFORMANCE PROPERTIES

Dry Time @ 77°F (25°C): 2-5 minutes

Dry Time @ 40°F (4°C): 5-10 minutes

Coverage per Gallon: 250-300 square feet

Min. Storage Temperature: 0°F (-18°C)

Min. Application Temperature: 40°F (4°C)

PHYSICAL PROPERTIES AND CHEMICAL COMPOSITION

Color: Clear

Solvent: Toluene

Flash Point: 0° F (-18° C)

Dried Surface: Clear, non-tacky

Shelf Life: 12 months after manufacture date



DIRECTIONS FOR USE

Surface Preparation: The concrete must be clean and free from dust, dirt, grease and debris before application of CS-80. Inspect surface for soundness. Repair or remove any surface irregularities and loose concrete, using an approved crack filling method on static hairline cracks. When the surface is clean, sound and dry, proceed with sealant application.

Application: Distribute the primer evenly across the concrete and wait for it to dry. Inspect the coated surface for any missed spots or voids. Apply only one coat of primer to the surface. Multiple coats may cause delamination. After use, immediately secure the primer's lid to prevent it from drying out.

LIMITED WARRANTY

This information is presented in good faith, but we cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with our products, may be used. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products, either alone or in combination with other products. Users are advised to make their own tests to determine the safety and suitability of each such product or product combinations for their own purposes. It is the **users' responsibility** to satisfy himself as to the suitability and completeness of such information for this own particular use. We sell this product without warranty, and buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of this product, whether used alone or in combination with other products.

© 2024 CONCRETE SEALANTS, INC.

CONCRETE SEALANTS, INC. | 9325 STATE ROUTE 201, TIPP CITY, OH 45371, USA | WWW.CONSEAL.COM

USA | CANADA +1.800.332.7325 INTERNATIONAL +1.937.845.8776

VERSION: 16-OCT-2024



CONCRETE SEALANTS, INC.
ISO 9001:2015 REGISTERED