SEAL OF SECURITY, BOND OF TRUST.

January 1, 2025

Certificate of Conformance

This is to certify that the material listed below conforms to the following specifications. The material meets or exceeds the listed requirements.

Product: ConSeal CS-1500 Rapid-Cure, Elastomeric Sealant

Specifications: This product meets or exceeds the requirements of ASTM C920, Type S, Grade NS, Class 50, Uses NT, M, G, A.

Chemical Composition and Physical Properties:

Vertical Displacement (ASTM C639): 3/16" max.
Shore A Hardness (ASTM C661): Less than 60

Effects of Heat Aging, % Weight Loss (ASTM C1246): 7% max. with no cracking or chalking

Tack-Free Time (ASTM C679): 72 hours max.

Stain and Color Change (ASTM C510): No stain or color change Adhesion and Cohesion Under Cyclic Movement (ASTM C719): 1.5 in.² max. area loss

Adhesion and Cohesion Under Cyclic Movement (ASTM C719): 1.5 in.2 max. area loss
Adhesion-in-Peel (ASTM C794): 5 lbf min. and 25% max. adhesive bond loss

Effects of Accelerated Weathering (ASTM C793): No cracking or chalking

Sincerely,

Daniel M. Sawhook, P.E. Technical Resource Engineer Concrete Sealants, Inc.



VERSION: 1-JAN-2025